4" and 6" LED Downlight Retrofit Kits





Energetic Lighting's ELDLf series of LED downlight retrofit kits provides an elegant solution for converting existing recessed cans into LED fixtures. Available in 4-inch and 6-inch can sizes operating at 7.5-watt, 11.5-watt, and 18-watt options, with a beam angle of 90°, and dimmable down to 10%. Comprising of a durable die-cast aluminum construction and a LED lifetime rating of at least 35,000 hours, this durable worklight is designed for many years of reliable operation.

















Features

- No UV or IR radiation
- Elegant and efficient design
- Mercury-free construction
- Suitable for Damp Location use
- Easy and secure installation

Applications

- Architectural decor
- Overhead accent lighting
- Spot area lighting
- General lighting

Please visit www.energeticlighting.com for Lighting Facts label, dimmer compatibility models, and other up-to-date information. Other color temperatures may be available by special request.

Specifications

	Can Size				6 ¹¹ Can Size			
	7		CRI-90				CRI-90	
Model:	ELDLf-EH4[W,S]TW	ELDLf-E4[W,S]TW	ELDLF-EH4[W,S]TW-R90	ELDLf-E4[W,S]TW-R90	ELDLf-EH6[W,S]TW	ELDLf-E6[W,S]TW	ELDLf-EH6[W,S]TW-R90	ELDLf-E6[W,S]TW-R90
Lumen Output:	700 lm	550 lm	680 lm	500 lm	1200 lm	750 lm	1000 lm	700 lm
Luminous Efficacy:	61 lm/W	73 lm/W	59 lm/W	67 lm/W	67 lm/W	65 lm/W	56 lm/W	61 lm/W
Beam Angle:	90°°	90°°	90°°	90°°	90°°	90°°	90°°	90°°
Input Power:	11.5 W	7.5 W	11.5 W	7.5 W	18 W	11.5 W	18 W	11.5 W
Input Voltage:	120 V ac	120 V ac	120 Vac	120 Vac	120 V ac	120 V ac	120 V ac	120 Vac
Power Factor:	≥95%	≥95%	≥95%	≥95%	≥95%	≥95%	≥95%	≥95%
THD:	<20%	<20%	<20%	<20%	<20%	<20%	<20%	<20%
CCT:	2700K,3000K [W,S]	2700K,3000K [W,S]	2700K,3000K [W,S]	2700K,3000K [W,S]	2700K,3000K [W,5]	2700K,3000K [W,S]	2700K,3000K [W,S]	2700K,3000K [W,5]
CRI:	>80	>80	>90	>90	>80	>80	>90	>90
R9:	1	4		3	3		71	72
Lifetime:	35000 hours	35000 hours	35000 hours	35000 hours				
Warranty:	5 Years	5 Years	5 Years	5 Years				
Dimmable:	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Operating Temp:	-4°Fto 104°F	-4°F to 104°F	-4°F to 104°F	-4°F to 104°F	-4°F to 104°F	-4°F to 104°F	-4°Fto 104°F	-4°F to 104°F
Environment:	Damp Rated	Damp Rated	Damp Rated	Damp Rated				
Weight:	0.4 lbs	0.4 lbs	0.4 lbs	0.4 lbs	0.62 lbs	0.62 lbs	0.62 lbs	0.62 lbs